

FLOODTITE

SYSTEMS

HOME FLOOD PROTECTION

AQUATITE TOILET PANSEAL



Tool requirements

- None, other than an ordinary bicycle pump or small air pump (Floodtite can provide a small air pump for £8 incl VAT and delivery – see www.floodtite.com)

Fitting Instructions for Floodtite's Aquatite Toilet 'Panseal'

- Floodtite's unique Aquatite 'Panseal' is specifically designed to prevent sewage backflow through the toilet system.
- Position the 'Panseal' just below the rim of the toilet.
- Inflate the 'Panseal' using an air pump until a firm seal is created. (The valve is the same as a bicycle or car valve). A watertight seal is achieved between the tubing and the inner wall of the pan and a secondary seal is formed underneath the rim.
- To deflate after use, press in the pin in the centre of the valve. You can use your finger or your fingernail or the tip of a biro.
- It is a good idea to practise installing the panseal to ensure you are familiar with its use, so that when you install it for a flood it is not your first time.
- After use, remember flood water and back flow water is potentially contaminated water. Always clean the product carefully after use with a disinfectant, and dry well.
- Store in a cool dry place that is easily accessible in the case of flood. Store away from sharp objects.
- A strong recommendation is to keep a small bicycle pump nearby so that it can be quickly used.
- Technical helpline: 07712 185240 email: tech@floodtite.com